



PUMPS & ACCESSORIES

Our farm supply and pump assortment is adapted to your need on your farm, quality and performance. Pumps help you to clean your farm easily. Find your pump for your needs. You are looking for a gas station or a gas pump? Our accessory is the right one for you.

Omnia 160/7 Auto submersible pump



- Submersible pump
- Stainless steel
- Used for clean and waste water
- Solid particles up to 20 mm diameter
- Carrying handle, cable, plug and float switch included
- Voltage: 230 V
- Max. liquid temperature: 40°C
- Max. depth of immersion: 7 m
- Min. draining level: 35 mm (manual)
- Connections: diameter 1" ¼ M
- Body/impeller: Stainless steel
- Accessories supplied: Connector
- Max. output: 160 L / min.
- Max. lift pressure: 7 m / 0,7 bar

Part no. N2081050 Omnia 160/7 Auto 1

Omnia 200/8 Auto submersible pump



- Submersible pump
- Stainless steel
- Used for clean and waste water
- Solid particles up to 20 mm diameter
- Carrying handle, cable, plug and float switch included
- Voltage: 230 V
- Max. liquid temperature: 40°C
- Max. depth of immersion: 7 m
- Min. draining level: 35 mm (manual)
- Connections: diameter 1" ¼ M
- Body/impeller: Stainless steel
- Accessories supplied: Connector
- Max. output: 200 L / min.
- Max. lift pressure: 8 m / 0,8 bar

Part no. N2081060 Omnia 200/8 Auto 1





Biox 200/8 Auto submersible pump



- Submersible pump
- Stainless steel
- Used for clean and waste water
- Solid particles up to 40 mm diameter
- Carrying handle, cable, plug and float switch included
- Voltage: 230 V
- Max. liquid temperature: 40°C
- Max. depth of immersion: 7 m
- Min. draining level: 45 mm (manual)
- Connections: diameter 1" ¼ M
- Body/impeller: Stainless steel
- Accessories supplied: Connector
- Max. output: 280 L / min.
- Max. lift pressure: 9 m / 0,9 bar

Part no. N2091020 Biox 200/8 Auto 1



Biox 400/12 Auto submersible pump



- Submersible pump
- Stainless steel
- Used for clean and waste water
- Solid particles up to 40 mm diameter
- Carrying handle, cable, plug and float switch included
- Voltage: 230 V
- Max. liquid temperature: 40°C
- Max. depth of immersion: 7 m
- Min. draining level: 45 mm (manual)
- Connections: diameter 1" ¼ M
- Body/impeller: Stainless steel
- Accessories supplied: Connector
- Max. output: 450 L / min.
- Max. lift pressure: 12 m / 1,2 bar

Part no. N2091060 Biox 400/12 Auto 1

Biox 300/10 Auto submersible pump



- Submersible pump
- Stainless steel
- Used for clean and waste water
- Solid particles up to 40 mm diameter
- Carrying handle, cable, plug and float switch included
- Voltage: 230 V
- Max. liquid temperature: 40°C
- Max. depth of immersion: 7 m
- Min. draining level: 45 mm (manual)
- Connections: diameter 1" ¼ M
- Body/impeller: Stainless steel
- Accessories supplied: Connector
- Max. output: 350 L / min.
- Max. lift pressure: 11 m / 1,1 bar

Part no. N2091040 Biox 300/10 Auto 1

SUB 3 S submersible pump



- Submersible pump
- Stainless steel
- Used for clean and waste water
- Solid particles up to 2 mm diameter
- Max. grain size: 2 mm
- Carrying handle, cable, plug and float switch included
- Accessories included: Connector for hoses diameter 13 mm, 19 mm, 25 mm
- Quantity of impellers: 3
- Voltage: 230 V
- Max. liquid temperature: 40°C
- Max. depth of immersion: 7 m
- Connections: diameter 1" ¼ M
- Body: Stainless steel
- Max. output: 100 L / min
- Max. lift pressure: 30 m / 3 bar

Part no. N3016120 Sub 3 S submersible pump 1



DRENOX 350/12 Auto submersible pump



- Submersible pump
- Stainless steel
- Used for clean and waste water
- Solid particles up to 6 mm diameter
- Max. grain size: 6 mm
- Carrying handle, cable, plug and float switch included
- Accessories included: Connector for hoses diameter 32 mm
- Quantity of impellers: 3
- Voltage: 230 V
- Max. liquid temperature: 40°C
- Max. depth of immersion: 7 m
- Connections: diameter 1" ¼ M
- Body: Stainless steel
- Max. output: 300 L / min.
- Max. lift pressure: 11 m

Part no. N1031080 Drenox 350/12 Auto 1

GASOIL STATION CT-KIT



- Powerful gasoil pump (Bypass), counter and gun mounted on wall panel
- Fuel filter is easy to clean
- Connection from bras
- Return valve with filter included
- Pump nozzle with swivel joint included
- Hose: 4 m
- Performance: 220 V / 370 W
- Max. output: 50 L / min.
- Max lift: 17 m

Part no. 18702-Set CT-Kit 1

PUMP DRILL 20



- Self-priming in both directions applicable pump
- Collectable with all drilling machines
- Decanting and transferring of liquids
- Usable for: Diesel, light oil, wine, most, vinegar, milk, etc.
- Max. output: 30 l / min.
- Max. lift: 25 m
- Max. suction lift: 6 m, self-priming

Part no. 16287 Pump Drill 20 1





BIO-DIESEL HOSE



- Rubberized Bio-Diesel hose
- Available as roll or in meters
- Price per meter
- Bio Diesel hose: 50 m per roll

Part no. 18554 Bio-Diesel hose 1

ACCESSORIES

	Part no.	Type	VPE
	88004	Return valve 3/4" With soaking basket	1
	82085	Socket in brass 1" External thread for diesel hose	1
	82086	Socket in brass 3/4" External thread for diesel hose	1

